

Test Report

No.: SDHGR120801924FT

Date: Sep.03, 2012

Page 1 of 2

TRADE SECRET

The following sample(s) was / were submitted and identified on behalf of the client as:

Sample Description

: HYDRAULIC BUFFERING HINGE

Buyer Item No.

: R093

Country of Destination

: USA

Test Performed

: Selected test(s) as requested by applicant

Sample Receiving Date

: Aug.22, 2012

Test Performing Date

: Aug.22, 2012 to Sep.03, 2012

Test Result(s)

: For further details, please refer to the following page(s)

Signed for and on behalf of SGS-CSTC Co., Ltd.

Jack Yao

Approved signatory

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions. htm and,for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, independent of any independent of the company is findings at the time of its interveption of the limitation of Client's Instructions, if any. The Company's sole responsibility is to its Client and this document does not exponse aparties to a transaction from expression gall their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any upwalhorized alteration, or greatly or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unloss otherwise stated the realits shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Alteration Total author the content of the c



Test Report

No.: SDHGR120801924FT

Date: Sep.03, 2012

Page 2 of 2


Test Conducted:

Clause 17.6 of ANSI/BIFMA X5.5-2008 DESK/TABLE PRODUCTS - TESTS

Test Item	Test Method & Requirement	Test Result
Wear and Fatigue Test for Hinged, Horizontally Sliding, and Tambour Doors. (Clause 17.6)	Cycle the testing door for a total of 50,000 cycles as specified. The cyclic rate shall be 12 \pm 4 cycles per minute unless the rate is controlled by the door operating mechanisms. After test, there shall be no loss of serviceability to the hinges.	Pass

Remark: When testing, the hinges to be tested were mounted to a testing door, the size of which is 750 mm in height and 368 mm in width.

Photo Appendix



End of Report

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/terms_and_conditions. htm and for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, independents and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its interveption of the William of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exponerate parties to a transaction from expressing all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any upsthorized alteration of the content or approval of the Company. Any upsthorized alteration of the content or approval of the Company. Any upsthorized alteration of the content or approval of the content or approval of the Company. Any upsthorized alteration of the content or approval of the Company. Any upsthorized alteration of the content of the law. Unless of the results are at the content of the content of the law.