

de**5. Störungen und ihre möglichen Ursachen**

Störung	Ursache	Abhilfe
Kühlschranktür öffnet nicht	Easys hat nach einem Stromausfall seinen Auslösehub vergessen	Kühlgerätetür von Hand öffnen, Netzkabel vom Strom nehmen und ca. 2 min warten, danach Netzstecker wieder ans Netz bringen. Das System fährt automatisch auf Werkseinstellung zurück (sechs langsame Fahrten des Öffnungsstößels - Dauer ca. 45 sec). Anschließend Kühlgerätetür wieder schließen und ca. 6 sec auf einen Doppelpiepton warten.
	Die automatische Fahrt des Systems zurück auf Werkseinstellung hat nicht stattgefunden	Kühlgerätetür von Hand öffnen, und System auf Werkseinstellung zurücksetzen. Hierfür per leichten Druck auf dem Sensor das System auslösen. Wenn Öffnungsstößel draußen, Stromzufuhr unterbrechen. Strom wieder auf das System bringen, das System meldet sich per doppeltem Dreifachpiepton. Der Öffnungsstößel fährt wieder ein. Wenn Stößel komplett eingefahren ist, Stromzufuhr erneut unterbrechen. Nach ca. 1-2 sec Strom wieder zuführen. Der Öffnungsstößel fährt sechs langsame Fahrten (heraus und rein, 3x hintereinander - Dauer ca. 45 sec). Anschließend Kühlgerätetür wieder schließen und ca. 6 sec auf einen Doppelpiepton warten. Sehen Sie hierzu auch den QR Code Reset auf der Vorderseite an.
	Die Stromzufuhr wurde bewusst unterbrochen	Falls Sie die Stromzufuhr unterbrechen müssen, tragen Sie dafür Sorge, dass die Kühlgerätetür vollständig geöffnet ist, bevor Sie das System wieder mit Strom versorgen!

en**5. Malfunctions and possible causes**


Malfunction	Cause	Remedy
Refrigerator door does not open	Easys forgot its trigger stroke after a power failure	Open the refrigerator door by hand, disconnect the power cord from the power supply and wait approx. 2 minutes, then reconnect the power plug. The system automatically returns to the factory setting (six slow movements of the opening piston - duration approx. 45 sec). Then close the refrigerator door again and wait approx. 6 seconds for a double beep.
	The system did not automatically move back to the factory settings"	Open the refrigerator door by hand and reset the system to the factory settings. To do this, trigger the system with light pressure on the sensor. If the opening piston is outside, switch off the power supply. Bring power back to the system, the system answers with a double triple beep. The opening piston retracts again. When the piston is completely retracted, interrupt the power supply again. Apply power again after approx. 1-2 sec. The opening piston makes six slow runs (out and in, 3 times in a row - duration approx. 45 sec). Then close the refrigerator door again and wait approx. 6 seconds for a double beep. See also the QR code reset on the front.
	The power supply was deliberately interrupted	If you have to interrupt the power supply, make sure that the cooling unit doors are fully opened before you restore power to the system!

de HINWEIS

Die Übersetzung in weitere Sprachen erfolgt mit dem nächsten Update der Montageanleitung!


en NOTE

The translation into other languages will take place with the next update of the assembly instructions!

Montage

[https://www.
hettich.com/
short/5663f7](https://www.hettich.com/short/5663f7)

Kurzanleitung zur Montage (Video als Download)
Krátký návod k montáži (video ke stažení)
Kort vejledning i montering (video til download)
Guía de montaje (vídeo para descargar)
Instructions de montage succinctes (vidéo à télécharger)
Asennusn piakohe (ladattava video)
Short installation guide (video for downloading)
Σύνοπτικές οδηγίες εγκατάστασης (βίντεο ως Download)
Kratke upute za montažu (preuzimanje video zapisa)
Rövid szerelési útmutató (letölthető videó)
Istruzioni di montaggio (Video disponibile per il download)
Trumpas diegimo instrukcijas (vaizdo įrašas kaip atsiuntimą)
Korte handleiding voor de montage (video om te downloaden)
Skrócona instrukcja montażu (film do pobrania)
Instruções rápidas de montagem (vídeo para download)
Instructiuni scurte pentru instalare (video ca download)
Краткая инструкция по монтажу (видео, доступное для загрузки)
Kort anvisning för monteringen (video att ladda ner)
Kratka navodila za montažo (video za prenos)
Krátky montážny návod (video na stiahnutie)
Montaj için kısa talimat (indirilebilir video)

Reset

[https://www.
hettich.com/
short/bde115](https://www.hettich.com/short/bde115)

Zurücksetzen auf Werkseinstellung
Obnovit tovární nastavení
Nulstil til fabriksindstillinger
Restablecer la configuración de fábrica
Rétablir les paramètres d'usine
Palauta tehdasasetuksiin
Reset to factory settings
Επαναφορά στις εργοστασιακές ρυθμίσεις
Vraćanje na tvorničke postavke
Gyári beállítások visszaállítása
Ripristina alle impostazioni di fabbrica
Grąžinti gamyklinius nustatymus
Resetten naar fabrieksininstellingen
Zresetuj do ustawień fabrycznych
Redefinir as configurações de fábrica
Resetați la setările din fabrică
Сброс к заводским настройкам
Återställ till fabriksinställningar
Obnoviť výrobné nastavenia
Ponastavite na tovarniške nastavitve
Fabrika ayarlarına sıfırla